

CLAIMS

1 1. An optical logic gate comprising:

2 a first digital input for receiving a first optical digital input signal;

3 a digital output for outputting an optical digital output signal which is a function of
4 the first optical digital input signal; and

5 a lasing semiconductor optical amplifier (LSOA) having an amplifier input and a
6 ballast laser output, the amplifier input and ballast laser output of the LSOA
7 coupled between the first digital input and the digital output.

1 2. The optical logic gate of claim 1 wherein the LSOA comprises:

2 a semiconductor gain medium;

3 an amplifying path coupled to the amplifier input and to an amplifier output and
4 passing through the semiconductor gain medium; and

5 a laser cavity including the semiconductor gain medium and coupled to the ballast
6 laser output.

7 3. The optical logic gate of claim 2 wherein the laser cavity has a laser threshold
whereby a ballast laser signal from the laser cavity is extinguished if the ballast laser signal
1 represents a digital zero.

1 4. The optical logic gate of claim 2 further comprising:

2 a gain element coupled between the ballast laser output of the LSOA and the digital
3 output of the optical logic gate for adjusting an amplitude of the ballast laser
4 signal so an amplitude of the optical digital output signal is the same as an
5 amplitude of the first optical digital input signal when the optical digital
6 output signal and the first optical digital input signal represent a same digital
7 logic level.

1 5. The optical logic gate of claim 1 wherein the optical logic gate is an optical NOT gate.

1 6. The optical logic gate of claim 5 wherein:

2 the first digital input of the optical logic gate is coupled to the amplifier input of the
3 LSOA;

4 the ballast laser output of the LSOA is coupled to the digital output of the optical
5 logic gate; and

6 the LSOA has a laser threshold whereby:

7 if the first optical digital input signal is a digital zero, a ballast laser signal from
8 the ballast laser output causes the optical digital output signal to be a
9 digital one; and

10 if the first optical digital input signal is a digital one, the ballast laser signal from
11 the ballast laser output causes the optical digital output signal to be a
12 digital zero.

13 7. The optical logic gate of claim 6 wherein the LSOA has the laser threshold whereby if
14 the first optical digital input signal is a digital one, the ballast laser signal is extinguished.

15 8. The optical logic gate of claim 1 wherein the optical logic gate is an optical NOR gate
16 further comprising:

17 a second digital input for receiving a second optical digital input signal.

18 9. The optical logic gate of claim 8 further comprising:

19 an optical combiner having two inputs and an output, the two inputs coupled to the
20 first digital input and to the second digital input, and the output coupled to the
21 amplifier input of the LSOA;

22 wherein the ballast laser output of the LSOA is coupled to the digital output of the
23 optical logic gate; and

24 wherein the LSOA has a laser threshold whereby:

25 if both the first and second optical digital input signals are a digital zero, a ballast
26 laser signal from the ballast laser output causes the optical digital output
27 signal to be a digital one; and

11 if at least one of the first and second optical digital input signals is a digital one,
12 the ballast laser signal from the ballast laser output causes the optical
13 digital output signal to be a digital zero.

1 10. The optical logic gate of claim 9 wherein the LSOA has the laser threshold whereby
2 if at least one of the first and second optical digital input signals is a digital one, the ballast laser
3 signal is extinguished.

1 11. The optical logic gate of claim 1 wherein the optical logic gate is an optical NAND
2 gate further comprising:

3 a second digital input for receiving a second optical digital input signal.

4 12. The optical logic gate of claim 11 further comprising:

5 an optical combiner having a first input and a second input and an output, the first
6 combiner input coupled to the ballast laser output of the first LSOA, and the
7 output coupled to the digital output of the optical logic gate; and

8 a second LSOA having an amplifier input coupled to the second optical digital input
9 and a ballast laser output coupled to the second combiner input.

10 wherein the first LSOA has a laser threshold wherein, response to the first optical
11 digital input signal being a digital signal:

12 if at least one of the first and second optical digital input signals is a digital zero, a
13 ballast laser signal from the ballast laser output causes the optical digital
14 output signal to be a digital one; and

1 if both the first and second optical digital input signals are a digital one, the
2 ballast laser signal from the ballast laser output causes the optical digital
3 output signal to be a digital zero.

4 13. The optical logic gate of claim 12 wherein:

5 in response to the first optical digital input signal being a digital one, a ballast laser
6 signal from first LSOA is a digital zero;

7 in response to the second optical digital input signal being a digital one, a ballast laser
8 signal from second LSOA is a digital zero;

6 in response to the first optical digital input signal being a digital zero, a ballast laser
7 signal from first LSOA is a digital one; and
8 in response to the second optical digital input signal being a digital zero, a ballast
9 laser signal from second LSOA is a digital one.

1 14. The optical logic gate of claim 1 wherein the LSOA is a vertical lasing
2 semiconductor optical amplifier (VLSOA).

1 15. The optical logic gate of claim 1 wherein the LSOA is a transverse lasing
2 semiconductor optical amplifier (TLSOA).

1 16. The optical logic gate of claim 1 wherein the LSOA is a longitudinal lasing
2 semiconductor optical amplifier (LLSOA).

3 17. An optical latch, comprising:

4 a set input;

5 a reset input;

6 a first output;

7 a second output;

8 a first lasing semiconductor optical amplifier (LSOA), comprising:

9 an input for receiving optical signals and connected to the set input; and

10 a laser output connected to the first output for outputting a first laser output
11 optical signal in response to the received optical signals;

12 a second LSOA, comprising:

13 an input for receiving optical signals and connected to the reset input and to the
14 laser output of the first LSOA; and

15 a laser output connected to the second output and to the input of the first LSOA
16 for outputting a second laser output optical signal in response to the
17 received optical signals;

18 wherein, in response to a high signal being input to the set input, and a low signal
being input to the reset input, reaching a first stable state where the first output
is low and the second output is high; and

19 wherein, in response to a high signal being input to the reset input, and a low signal
20 being input to the set input reaching a second stable state where the first
21 output is high and the second output is low.

1 18. The optical latch of claim 17, wherein the first LSOA further comprises:
2 a laser cavity with an optical path;
3 an amplifying path connected to the input and passing through the laser cavity for
4 propagating the optical signals received at the input;
5 a pump input connected to the laser cavity for receiving a pump for exceeding a
6 lasing threshold for the laser cavity; and
7 wherein the laser output outputs the first laser output optical signal in response to the
8 received optical signals propagating through the amplifying path.

9 19. The optical latch of claim 17, further comprising:
10 a first combiner connected to the set input, the input of the first LSOA, and the laser
11 output of the second LSOA for receiving optical signals from the set input and
12 the laser output of the second LSOA and outputting a combined optical signal
13 to the input of the first LSOA; and
14 a second combiner connected to the reset input, the input of the second LSOA, and
15 the laser output of the first LSOA for receiving optical signals from the set
16 input and the laser output of the first LSOA and outputting a combined optical
17 signal to the input of the second LSOA.

1 20. The optical latch of claim 17, further comprising:
2 a first splitter connected to the laser output of the first LSOA, the input of the second
3 LSOA, and the first output for receiving optical signals from the laser output
4 of the first LSOA and outputting the received optical signals to the input of
5 the second LSOA and the first output; and
6 a second splitter connected to the laser output of the second LSOA, the input of the
7 first LSOA, and the second output for receiving optical signals from the laser

8 output of the second LSOA and outputting the received optical signals to the
9 input of the first LSOA and the second output.

1 21. An optical logic gate, comprising:

2 a lasing semiconductor optical amplifier (LSOA) having an amplifier input, a ballast
3 laser output, and an amplifier output;

4 a time delay having an input coupled to the ballast laser output for receiving a ballast
5 laser output signal, an output coupled to the amplifier input for, at a later time,
6 sending the ballast laser output optical signal to the amplifier input; and

7 a digital output coupled to the amplifier output for outputting a periodic substantially
8 square waveform optical signal.

9 22. The optical logic gate of claim 21, wherein the time delay is a length of optical fiber.

10 23. The optical logic gate of claim 21, wherein the time delay is silicon.

11 24. The optical logic gate of claim 21, the LSOA further comprising a laser cavity with
12 an optical path having a variable optical path length.

13 25. The optical logic gate of claim 24, the laser cavity of the LSOA further comprising:
14 a first mirror; and

15 a second mirror separated from the first mirror by a distance, the distance being variable.

16 26. The optical logic gate of claim 25, wherein the first mirror is a micro electro-
17 mechanical system (MEMS) mirror with a variable position.

18 27. The optical logic gate of claim 26, the LSOA further comprising a conducting layer
19 for varying the position of the first mirror by applying a selected voltage between the first mirror
20 and the conduction layer.

21 28. The optical logic gate of claim 21, the LSOA further comprising a tunable region
22 with a selectable refractive index.

23 29. The optical logic gate of claim 21, the time delay being a variable time delay.

